



## STINGER™ DISSOLVABLE FRAC PLUG

This product may be covered by one or more patents or pending patent applications.

### FIELD-PROVEN FOR FASTER AND GREATER SAVINGS.

Delivering the most advanced dissolvable technology in the industry, the Stinger Dissolvable Plug from Nine provides greater savings in multi-well plug-and-perf operations. And currently, it offers the leading solution to work consistently and predictably in all temperature applications.

By dissolving, operators avoid the time, risks and costs associated with conventional completions—operators save in upfront Authorization for Expenditure (AFE) costs. Because they get to production faster, operators also see an Increased Rate of Return (IRR). The Stinger also eliminates the need for coil, which can result in weeks of downtime and up to \$1 million in costs if stuck downhole.

The Stinger is the shortest available, featuring a single as opposed to dual slips. This design is made possible thanks to the unique sealing mechanism that eliminates the need for a mandrel and allows for a smaller element, improving dissolution.

The Stinger features a larger ID to accommodate immediate flowback and freshwater magnesium, which works in all environments, including high-chloride reuse water.

### Features

- Compact and robust design
- Standard RIH conveyance method
- Ceramic gripping buttons
- Reduces the need for coiled tubing intervention
- Ball in Place models for water savings

The Stinger™ is the industry's shortest and most advanced dissolvable technology available.

Casing Size inch (mm)	Casing Weight lbs/ft (kg/m)	Casing I.D. inch (mm)	Tool Description	Tool Gauge O.D. inch (mm)	Tool I.D. inch (mm)	Overall Length (After set)	Overall Length RIH inch (mm)	Ball Size inch (mm)	Pressure Rating psi (MPa)
5-1/2 (139.7)	20-23 (29.8-34.2)	4.778-4.670 (121.36-118.62)	Ball in Place	4.37 (111.0)	1.5 (38.1)	3.5 (88.89)	5.77 (146.6)	1.75 (44.45)	10,000 (69)
								9,000 (62)	
	Ball Drop	2.5 (63.5)	10,000 (69)						
			9,000 (62)						
	15.5-17 (23.1-25.3)	4.950-4.892 (125.73-124.26)	Ball in Place	4.5 (114.3)	1.5 (38.1)			1.75 (44.45)	10,000 (69)
								9,000 (62)	
Ball Drop	2.5 (63.5)	10,000 (69)							
		9,000 (62)							

Casing Specs are according to API Tubing/Casing Dimension Chart Information.

For more information, and to find a representative near you, visit [nineenergyservice.com](http://nineenergyservice.com)